

IN THE CLAIMS

Please amend the claims as follows.

1. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, high pressure water is jetted obliquely rearward from a plurality of injection holes opened in the nozzle, a propulsion force is generated in the nozzle by that jetting force, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the high pressure water jetted from the nozzle, characterized in that:

the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning and pulling out of the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe.

2. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, high pressure water is jetted obliquely rearward from a plurality of injection holes opened in the nozzle, a propulsion force is generated in the nozzle by that jetting force, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and interior of the pipe is washed by the high pressure water jetted from the nozzle, characterized in that:

the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning and

pulling out of the high pressure hose, said movement being generated by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is set so as to be larger than diameters of other injection holes; and

angle α subtended by center axis line I of the certain injection hole and center axis line H of the nozzle is set so as to be smaller than angle β subtended by a center axis line J of other injection holes and ~~the~~ a center axis line H of the nozzle (so that ~~$\alpha < \beta$~~ α is less than β).

3. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, high pressure water is jetted from a plurality of injection holes opened in the nozzle, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the high pressure water jetted from the nozzle, characterized in that:

the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning, pulling out, and pulling back of the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is set so as to be larger than diameters of other injection holes; and

angle α subtended by center axis line I of the certain injection hole and center axis line H of the nozzle, and angle β subtended by a center axis line J of other injection holes and ~~the~~ a

center axis line H of the nozzle, respectively, are each set to 90 degrees.

4. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, high pressure water is jetted from a plurality of injection holes opened in the nozzle, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the high pressure water jetted from the nozzle, characterized in that:

the nozzle is made to turn in a spiral ~~manner~~ movement along inner peripheral surface of the pipe, in conjunction with turning and feeding out the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is made larger than diameters of other injection holes;

a position of the certain injection hole is made farther rearward than positions of other injection holes as seen from direction of advance of the nozzle;

angle a subtended by center axis line I of the certain injection hole and center axis line H of the nozzle is made an acute angle; and

angles ~~13~~ β subtended by center axis line J of other injection holes and ~~the~~ a center axis line H of the nozzle, respectively, are each set at substantially 90 degrees.

5. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal

guide is linked to a leading end of the nozzle, a jetting medium is jetted obliquely rearward from a plurality of injection holes opened in the nozzle, a propulsion force is generated in the nozzle by that jetting force, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the jetting medium jetted from the nozzle, characterized in that:

the jetting medium ~~is constituted by~~ comprises a mixture of a fluid and a gas; and
the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning and pulling out of the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe.

6 (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, jetting medium is jetted obliquely rearward from a plurality of injection holes opened in the nozzle, a propulsion force is generated in the nozzle by that jetting force, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the jetting medium jetted from the nozzle, characterized in that:

the jetting medium ~~is constituted by~~ comprises a mixture of a fluid and a gas;
the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning and pulling out of the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is set so as to be larger than diameters of other injection holes; and

angle α subtended by center axis line I of the certain injection hole and center axis line H of the nozzle is set so as to be smaller than angle β subtended by center axis line J of other injection holes and the center axis line H of the nozzle (so that $\alpha < \beta$ α is less than β).

7. (Currently amended) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, jetting medium is jetted from a plurality of injection holes opened in the nozzle, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the jetting medium jetted from the nozzle, characterized in that:

the jetting medium ~~is constituted by~~ comprises a mixture of a fluid and a gas;

the nozzle is made to turn in a spiral ~~manner~~ movement along inner peripheral surface of the pipe, in conjunction with turning, pulling out, and pulling back the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is set so as to be larger than diameters of other injection holes; and

angle α subtended by center axis line I of the certain injection hole and center axis line H of the nozzle, and angle β subtended by a center axis line J of other injection holes and ~~the~~ a center axis line H of the nozzle, respectively, are each set to 90 degrees.

8. (Original) A method of washing drain pipe in which a nozzle is provided at leading end of a high pressure hose connected to a terminal hose control, a universal guide is linked to a leading end of the nozzle, jetting medium is jetted from a plurality of injection holes opened in the nozzle, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and the interior of the pipe is washed by the jetting medium jetted from the nozzle, ~~in which a nozzle is provided at leading end of a high pressure hose, a universal guide is linked to leading end of the nozzle, jetting medium is jetted obliquely rearward from a plurality of injection holes opened in the nozzle, a propulsion force is generated in the nozzle by that jetting force, the high pressure hose is fed into a drain pipe while causing the high pressure hose to turn, and interior of the pipe is washed by the jetting medium jetted from the nozzle,~~ characterized in that:

the jetting medium ~~is constituted by~~ comprises a mixture of a fluid and a gas;

the nozzle is made to turn in a spiral ~~manner~~ movement in conjunction with turning and feeding out the high pressure hose, said movement being generated solely by the terminal hose control and the propulsion force, so that, of the plurality of injection holes, only a certain injection hole is always in opposition to the inner peripheral surface of the pipe;

the diameter of the certain injection hole is made larger than diameters of other injection holes;

the position of the certain injection hole is made farther rearward than positions of other injection holes as seen from direction of advance of the nozzle;

angle α subtended by a center axis line I of the certain injection hole and a center axis line H of the nozzle is ~~made~~ an acute angle; and

angles β subtended by center a axis line J of other injection holes and ~~the~~ a center axis

line H of the nozzle, respectively, are each set at substantially 90 degrees.

9. (Previously amended) The method of washing drain pipe according to claim 1, characterized in that the high pressure water is hot water.

10. (Previously amended) The method of washing drain pipe according to claim 5, characterized in that the fluid is cold water or hot water, and the gas is air.

11. (Previously amended) The method of washing drain pipe according to claim 1, characterized in that diameter of the certain injection hole is set so as to be larger than diameters of other injection holes.

12. (Previously amended) The method of washing drain pipe according to claim 1, characterized in that the nozzle and the high pressure hose are directly linked by means of a pressure connection socket.

13. (Currently amended) The method of washing drain pipe according to claim 1, characterized in that a reference line is placed on the surface of the high pressure hose indicating a position of the certain injection hole ~~is formed on surface of the high pressure hose,~~ along the longitudinal direction thereof.

Claims 14-26 (Cancelled)